



## GBTouch 24C

### Industrial all-in-one > TOUCH TERMINAL

GBTouch is the ideal solution for the needs of displaying corporate ERP systems, work documentation, operating instructions, production operations and machine control. It finds utilization as an indispensable working tool for smart production "Industry 4.0" connecting digital and real operation. Digitize right now, reduce production costs and accelerate the efficiency and flexibility of production processes.

The advantages of GBTouch terminals are maintenance-free operation, low operating costs and adaptation to customer requirements. Thanks to its robust construction and durability, the use of this device is possible in almost any environment.

The compact design ensures that it takes up only the most necessary space in the workplace.



- > Rugged terminal with 24/7 operation guarantee
- > 24" Full HD display, 1920 x 1080 resolution
- > PCAP Projected Capacitive touchpad
- > Powerful industrial PC Intel Gemini Lake
- > Passive cooling ensures trouble-free operation in a dusty environment
- > SSD disk for fast data transfer
- > Integrated dual RFID reader 125 kHz/13,56 MHz
- > Low power consumption
- > Superior service support and warranty
- > Possibility of individual adjustments according to the customer's wishes
- > Optional frame color and mounting
- > Durable aluminum construction
- > Choice of operating system
- > Made in the Czech Republic

[www.gbtouch.cz](http://www.gbtouch.cz)

# Technical specifications > GBTouch 24C

Display size	24" / 60,9 cm
Touch screen	PCAP (Projected Capacitive)
LED Display	LED Full HD 16:9
Resolution	1920 x 1080 @ 60 Hz
Brightness	250 cd/m <sup>2</sup>
Monitor size (H x W x D)	582 x 352 x 75 mm
Processor	Intel Gemini Lake, passive cooling
RAM	8 GB SDRAM DDR4 (max. 16 GB)
HDD	SSD 128 GB M.2 (expandable)
Interface	2x LAN RJ45, 4x USB 2.0, 1x RS-232, 2x DisplayPort
RFID	GABEN dual reader 125 kHz / 13,56 MHz
Connectivity	Wi-Fi modul Dual Band Wireless
Terminal weight	8 kg
Operating system	Microsoft® Windows™ 10 Professional Microsoft® Windows™ IoT Linux

## Other parameters

Power supply	8-24 V
Operating temperature	0 °C to +60 °C
Monitor cover color / mounting	selectable from color chart RAL/stainless steel design
Mounting	VESA (100 x 100 mm)

## Optional accessories

Mounting options	barcode reader, label printer, expansion modules stand, wall, kiosk, trolley, (according to requirements)
------------------	--

  
**Gaben**

Manufacturer: **GABEN, spol. s r.o.**  
Hájkova 1/558, 702 00 Ostrava  
Czech Republic

Phone: **+420 602 507 400**  
E-mail: **info@gaben.cz**  
Web: **www.gaben.cz**



© GABEN, spol. s r.o., All rights reserved



[www.gbtouch.cz](http://www.gbtouch.cz)

Everything for automatic identification since 1991